

## MEGAMAT 2

### Article number: 58795

MCZ/GY/710-500/F/2.0/24  
LS/IPX6

|                               |                                     |
|-------------------------------|-------------------------------------|
| COLOUR                        | grey                                |
| COLOUR CODE                   | RAL 7035                            |
| ACTUAL INSTALLATION DIMENSION | 709.5 [mm]                          |
| ACTUAL STROKE                 | 500.0 [mm]                          |
| PUSH FORCE                    | 2.00 [KN]                           |
| PULL FORCE                    | 2.00 [KN]                           |
| MEMORY                        | no                                  |
| MECHANICAL RELEASE            | no                                  |
| INPUT VOLTAGE                 | 24 [V]                              |
| PLUG TYPE                     | Loudspeaker                         |
| MAINS CABLE CONNECTION TYPE   | Fixed cable                         |
| CABLE STYLE                   | Coiled                              |
| CABLE LENGTH                  | 455 [mm]                            |
| GEAR CLEVIS HOLE              | 10.1 [ø mm]                         |
| GEAR CLEVIS SLOT              | 5.1 [mm]                            |
| GEAR CLEVIS POSITION          | 0 [°]                               |
| STROKE PIPE CLEVIS HOLE       | 10.1 [ø mm]                         |
| STROKE PIPE CLEVIS SLOT       | 5.4 [mm]                            |
| SPINDLE NUT                   | Fixed                               |
| SAFETY SPINDLE NUT            | no                                  |
| PULL-OUT PROTECTION           | no                                  |
| CLAMPING PROTECTION           | n/a                                 |
| DYNAMIC BRAKE                 | no                                  |
| DAMPING SPRING                | no                                  |
| OVERCURRENT SWITCH-OFF        | no                                  |
| IP PROTECTION TYPE            | IP66                                |
| UL/ETL                        | no                                  |
| TRANSPORT/STORAGE TEMPERATURE | -20 °C to +50 °C / -4 °F to +122 °F |